

RPI Re-Flex TPO Cover Tape Data Sheet

Re-Flex Tape	
PHYSICAL PROPERTIES	
BASE:	RUBBER POLYMER
COLOR:	WHITE
SOLVENTS:	NONE
PERCENT SOLIDS:	98 %
CURED STATE:	CURED
THICKNESS:	.030" ± .005"
WIDTH:	6.5"
LENGTH:	100 LF
Re-Flex TPO	
PHYSICAL PROPERTIES	
BASE:	TPO
COLOR:	WHITE
SOLVENTS:	NONE
PERCENT SOLIDS:	100 %
THICKNESS:	.045" ± 10 %
WIDTH:	6"+ 0", -1/8"
LENGTH:	100 LF



DESCRIPTION:

RPI Re-Flex TPO Cover Tape is a white TPO membrane developed for use with Re-Flex TPO System. Re-Flex TPO Cover Tape is a laminate of Re-Flex TPO and Re-Flex Seam Tape. It is used to flash in metal edge, gravel stop, and other details as outlined in RPI TPO Specifications.

APPLICATION INSTRUCTIONS

Installation of Re-Flex TPO Cover Tape:

1. All metal flashings and membranes must be free from dust, dirt, and oils. If the surfaces are contaminated, clean using Royal Edge Membrane Cleaner.
2. Using an RPI Scrub Pad, apply Re-Flex Primer/Activator to the surface to receive the Cover Tape.
3. Check Primer/Activator using the finger push test. Primer should be tacky, but not wet. Position the Cover Tape and remove the release paper. Roll the entire Cover Tape with a hand roller, first rolling across the Cover Tape, then the length of the Cover Tape.

It is important to completely hand-roll all tape details.

PRODUCT CODE:

TCT6100/TCT5050

PACKAGING:

Roll Size: 6 "(inch) X 50 ft. rolls 2 rolls per carton
Weight: 24 lbs per carton

RECOMMENDED STORAGE:

1. When stored in original unopened containers at temperatures between 60° F (15.6°C) and 80° F (26.7°C), a shelf life of 12 months can be expected. The expected shelf life can be shortened if product is stored in temperatures exceeding recommended storage levels.
2. Store in unopened cartons protected from weather.

PRECAUTION DATA:

1. Refer to Material Safety Data Sheets for specific requirements.

Information stated on this Roofing Products International, Inc. Data Sheet is intended to provide basic guidance as to storage, application, coverage, shipping, and other product data. Information is subject to change without notice. For more information regarding this product, refer to RPI MSDS, and the RPI Specification Manual. As neither Roofing Products International, Inc. nor its representatives practice structural engineering or architecture, RPI disclaims any responsibility and offers no opinion as to the structural soundness of any structure on which its products may be applied. The building owner should obtain the services of a competent structural engineer before proceeding. RPI accepts no responsibility for any structural failure or resultant damages. No Roofing Products International, Inc. representative is authorized to vary this disclaimer.