

RPI ROYAL EDGE LOW VOC MEMBRANE CLEANER TECHNICAL DATA SHEET

PRODUCT DATA	
VISCOCITY: Thin Free Flowing	WEIGHT: 6.20 lb/gal @ 77 °F
COLOR: Clear	SOLVENTS: Aliphatic Hydrocarbon
BOILING POINT: 247° F (119.4° C)	SPECIFIC GRAVITY: 0.75 (nominal)
DOT Label Required: Flammable Liquids	FLASH POINT F (SETA) 55°F (12.8° C)



DESCRIPTION:

RPI Royal Edge Low VOC Membrane Cleaner is a solvent based all purpose cleaning agent designed to clean single ply membranes prior to applying splice adhesives. Also used for cleaning metal edge and other metal flashings prior to applying Seam Tape Primer and Tape backed products.

Refer to the RPI Specification Manual for details.

APPLICATION INSTRUCTIONS:

Apply Membrane Cleaner using a clean, white cotton rag. Saturate the rag with Membrane Cleaner and scrub the membrane with a circular motion until all dirt, dust, and debris is removed. The surface should dry to a uniformly clean, smooth sheen without streaks. Wear protective eyewear and gloves.

PRECAUTION DATA:

1. **The solvents used in this product are extremely flammable.** Do not smoke when using. Keep away from open flames, sparks, and other sources of ignition.
2. Avoid contact with skin and eyes. Protective eyewear along with OSHA approved gloves should be worn.
3. Avoid breathing vapors.
4. Use only in well ventilated areas.
5. Keep containers closed when not in use.
6. Refer to Material Safety Data Sheet (MSDS) for additional precautionary information.

COVERAGE RATES :

Estimated coverage is 200-250 square ft. per gallon.

PACKAGING:

Available in:

- | | |
|----------------|---------------------|
| 1 gallon pails | 8-pails per carton |
| 5 gallon pails | 45 pails per pallet |

DOT LABEL REQUIRED:

Flammable Liquid

SHELF LIFE :

1. When stored in original unopened containers at temperatures between 60° F (15.6° C) and 80° F (26.7° C), a shelf life of 12 months can be expected.
2. The expected shelf life can be shortened if the product is stored at temperatures exceeding the recommended storage temperatures.

RECOMMENDED STORAGE:

1. Store in original unopened containers at temperatures between 60° F and 80° F.
2. Do not allow material to be stored or exposed to direct sunlight until ready to use. Rotate stock.
3. Keep away from open flames and other sources of ignition.
4. When stored in cooler temperatures, restore product to room temperature before use.

Information stated on this Roofing Products International, Inc. Data Sheet is intended to provide basic guidance as to storage, application, coverage, shipping, and other product data. Information is subject to change without notice. For more information regarding this product, refer to RPI MSDS, and the RPI Specification Manual. As neither Roofing Products International, Inc. nor its representatives practice structural engineering or architecture, RPI disclaims any responsibility and offers no opinion as to the structural soundness of any structure on which its products may be applied. The building owner should obtain the services of a competent structural engineer before proceeding. RPI accepts no responsibility for any structural failure or resultant damages. No Roofing Products International, Inc. representative is authorized to vary this disclaimer.