

ROYAL EDGE CURED COVER STRIP WITH TAPE TECHNICAL DATA SHEET

PRODUCT DATA

Royal Edge Seam Tape

PHYSICAL PROPERTIES

BASE:	RUBBER POLYMER
COLOR:	BLACK
SOLVENTS:	NONE
PERCENT SOLIDS:	100 %
CURED STATE:	CURED
THICKNESS:	.045" ± .005"
WIDTH:	5 1/4"
LENGTH:	100 LF

Royal Edge EPDM Flashing

BASE:	EPDM
COLOR:	BLACK
SOLVENTS:	NONE
PERCENT SOLIDS:	100 %
CURED STATE:	SEMI-CURED
THICKNESS:	.045" ± 10 %
WIDTH:	5" + 0", -1/8"
LENGTH:	100 LF



DESCRIPTION:

RPI Royal Edge Self-Adhering Cover Strip is a black EPDM membrane developed for use with RPI EPDM Systems. Royal Edge Self-Adhering Cover Strip is a laminate of Royal Edge semi-cured EPDM and Royal Edge Seam Tape. It is used to flash in metal edge, gravel stops, and other details as outlined in RPI System Specifications.

APPLICATION INSTRUCTIONS:

Installation of RPI Self-Adhering Cover Strip:

1. All metal flashings must be free from dust, dirt, and oils. To remove any residual manufacturing oils, clean metal flashings with RPI Membrane Cleaner.
2. Use RPI Scrub Pad to apply RPI Seam Tape Primer to metal flashings and membranes.
3. Install RPI Self-Adhering Cover Strip over cleaned and primed areas. Refer to RPI Installation details.

NOTE: RPI Scrub Pads are supplied separately.

PACKAGEING:

1. 2 -100 ft. rolls per carton
2. 36 cartons per pallet.

PRECAUTION DATA:

1. Refer to Material Safety Data Sheets for specific requirements.

RECOMMENDED STORAGE:

1. Store in original unopened containers at temperatures between 60° F (15.6°C) and 80° F (26.7 C).
2. The expected shelf life can be shortened if product is stored in temperatures exceeding recommended storage levels. Do not store in direct sunlight.
3. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE:

1. When stored indoors in original unopened containers at temperatures between 60° F (15.6° C) and 80° F (26.7° C), a shelf life of 6 to 9 months can be expected.
2. Product shelf life will be shortened if exposed to elevated temperatures.



Information stated on this Roofing Products International, Inc. Data Sheet is intended to provide basic guidance as to storage, application, coverage, shipping, and other product data. Information is subject to change without notice. For more information regarding this product, refer to RPI MSDS, and the RPI Specification Manual. As neither Roofing Products International, Inc. nor its representatives practice structural engineering or architecture, RPI disclaims any responsibility and offers no opinion as to the structural soundness of any structure on which its products may be applied. The building owner should obtain the services of a competent structural engineer before proceeding. RPI accepts no responsibility for any structural failure or resultant damages. No Roofing Products International, Inc. representative is authorized to vary this disclaimer.



57460 Dewitt St. Elkhart, IN 46517

Sales/Technical 1-800-628-2957 Fax: 574-294-3450 www.rpiroyaledge.com