



57460 Dewitt Street ■ Elkhart, Indiana 46517-1078  
Phone (574) 293-9096 ■ Fax (574) 294-3450  
800-628-2957 ■ Web site: www.rpiroyaledge.com



## RPI RE-FLEX COATING CARE AND MAINTENANCE PROCEDURE

*CONGRATULATIONS on your purchase of an R.P.I. Re-Flex Coating Roofing System. Your roof is a valuable asset which must be properly maintained to ensure it performs as designed.*

1. Ensure that the *Re-Flex Coating Membrane* is not exposed to liquids such as solvents, greases, oils, and petroleum-based products. These products will adversely affect the membrane.

**NOTE:** *Should the Re-Flex Coating come in contact with any of these substances, immediately clean the area with membrane cleaner.*

2. Ensure that ponding water (defined as 1/8" deep standing water on any area of the roof forty-eight (48) hours after it stops raining) is not allowed on the roof. Ponding water is a detriment to any flat roof and cannot be allowed to persist.
3. Ensure that all drain areas and drains are cleaned on a regular basis. This will allow for proper water runoff and avoid overloading the roof with ponding water.
4. Keep all counter flashing, metal work, drains, equipment curbs and supports, and any other rooftop accessories functioning in conjunction with the roofing system properly maintained at all times. R.P.I. encourages an annual roof inspection program be arranged by your contractor.
5. If there is to be foot traffic on the roof for any reason, on a regular basis (30 days or less in frequency), contact your applicator before proceeding for the installation of protective walk way pads.
6. Caution all tradesmen servicing roof equipment that you have an *Re-Flex Coating* roof, and that they should proceed accordingly.
7. Should there be an addition to the building, requiring a tie-in to the R.P.I. *Re-Flex Coating* material, contact R.P.I. to ensure the tie-in is in accordance with R.P.I. specifications.

**NOTE:** *Do not use asphalt roof cement for installation or repair of Re-Flex Coating or flashings, as it contains petroleum products that may damage the Re-Flex Coating or Re-Flex flashings.*

**R.P.I. believes the foregoing procedures will assist you, the building owner, in maintaining a watertight roof and in obtaining the maximum return on your investment in R.P.I.'s Re-Flex Coating installation. Remember, maintenance is not only essential, it is required.**

**Owner or Designate signature required to initiate warranty.**

**Thank you for your assistance.**

**Submit signed copy within 30 days to:**

**Attn: Warranty Processing Department  
Roofing Products International, Inc.  
57460 Dewitt Street  
Elkhart, IN 46517-1078**