

acc. to OSHA HCS

Revision Number 3

Page 1/8

Ariticle Number 402

Revision Date 01/05/2016

Section 1. Identification Product

identifier: Fabric

- **Trade name:** Re-Flex Flashing Fabric
- Product Code: RFF
- Chemical Name: Polyethylene terephthalate polymer
- Relevant identified uses of the substance or mixture: Construction

Details of the supplier of the safety data sheet

- *Manufacturer/Supplier: Roofing Products International, Inc. 57460 Dewitt St. Elkhart, IN 46517-1078*
- Information department: Technical Services Department

Emergencytelephone number

ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887

Section 2. Hazard(s) identification

Classification of the substance or mixture

Warning statements

None

Precautionary statements

If medical advice is needed, have product container or label at hand.Keep out of reach of children.Read label before use. Wear protective gloves and eye safety glasses.Do not use in areas without proper ventilation.INGESTION:Considered unlikely.SKIN CONTACT:Possible irritation.Rinse skin with water/shower.EYE CONTACT:Mechanical irritationINHALATION:Not considered an inhalation hazard.Store in a well ventilated, cool area. Store in tightly sealed original containers.Dispose of contents/container in accordance with local/regional/national/international regulations.In case of fire use for extinction:CO2, powder or foam.

Refer to Section 11 for toxicological information.

Classification system

• NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 1\\ Fire = 0\\ Reactivity = 0 \end{array}$

• HMIS-ratings (scale 0 - 4)

 HEALTH
 1
 Health = 1

 FIRE
 0
 Fire = 0

 PHYSICAL HAZARD
 Physical Hazard = 0

Other hazards

Results of PBT and vPvB assessment:

- **PBT:** Not applicable.
- vPvB: Not applicable.

(Contd. on page 2)

acc. to OSHA HCS

Ariticle Number 402

Revision Number 3

Page 2/8

Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

(Contd. of page 1)

Section 3. Composition/information on ingredients

• Chemical characterization: Mixtures

• Description: White, moderately thick liquied with mild ammonia odor.

Components	CAS Number	% by Weight
Acrylic co-polymer	Not established	20±5%
Fillers and extenders	Mixture	40 ± 5%
Tetrachloroisophthalonitrile (biocide)	1897-45-6	1 ± 0.5%
Water	7731-18-5	40 ± 5%

Note: The above components and their percentages are provided for health and safety purposes, only. This document should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

Components referred to herein may be regulated by specific Canadian provincial legislation. Please refer to exposure limits legislated for the province inwhich the substance will be used.

Section 4. First-aid measures

Description of first aid measures

• After inhalation:

Not expected to be an inhalation hazard.

- Afterskin contact: Remove contaminated clothing and wash affected area with soap and water. Rinse affected area with clean water for 15 minutes. Wash clothing before reuse.
- After eye contact:
 Immediately flush

Immediately flush opened eye for several minutes under clean running water. Eye lids should be held away from the eyeball to ensure thorough rinsing. Get medical attention if irritation persists.

• *After swallowing:* Not expected to be an ingestion hazard.

Most important symptoms and effects, both acute and delayed

- *Eye Contact: Causes irritation.*
- Inhalation: Harmful if inhaled.
- *Skin Contact: May cause skin irritation.*
- Ingestion: Irritating to mouth, throat, and stomach.

Over-exposure signs and symptoms

- Eye Contact
- Adverse symptoms may include the following: Pain or irritation. Redness and watering of the eyes.
- Inhalation
- Adverse symptoms may include the following: Nausea or vomiting, headache with drowsiness or fatigue.
- Skin Contact
- Adverse symptoms include the following: Irritation and redness.
- Ingestion
- Adverse symptoms may include the following: Nausea and/or vomiting.

Indication of any immediate medical attention and special treatment needed Information for Physician

(Contd. on page 3)

acc. to OSHA HCS

Ariticle Number 402

Revision Number 3

Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

If ingested, this material presents a aspiration hazard.

- *Specific treatments: Treat symptomatically and supportively.*
- **Protection of first aiders:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth to mouth resuscitation.

Section 5. Fire-fighting measures

Extinguishing media

- *Suitable extinguishing agents: CO2, sand, extinguishing powder.*
- For safety reasons unsuitable extinguishing agents: None determined.

Advice for firefighters

• Protectiveequipment:

Mouth respiratory protective device. Protective clothing and respiratory protective device.

Section 6. Accidental release measures

Personal precautions, equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Recover free product and dispose according to local, state, and federal regulations. Ventilate confined spaces.

Advise authorities is product has entered sewers, waterways or extensive land areas.

If your facility or operation has an "oil or hazardous substance contingency plan", activate the procedure. Take immediate steps to stop and contain the spill and shut off all sources of ignition.

• Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Prevent seepage into sewage system, workpits and cellars. Do not allow product to reach sewage system or any water course. Do not allow to enter sewers/surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Section 7. Handling and storage

• Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Wear personal protective equipment. Open and handle receptacle with care. Do not use air pressure to unload containers. Keep container tightly closed.

(Contd. on page 4)

(Contd. of page 2)

Page 3/8

acc. to OSHA HCS

Ariticle Number 402

Revision Number 3

Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

(Contd. of page 3)

Section 8. Exposure controls/personal protection

Additional information about design of technical systems Nofurther data; see item 7.

Control parameters

• Components with limit values that require monitoring at the workplace:

This product does not contain any relevant quantities of materials with critical values that have to be montored at the workplace.

• *Additional information: The lists that were valid during the creation were used as basis.*

Exposure controls

Personal protective equipment (see listings below)

General protection and hygiene

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Store protective clothing separately. Breathing equipment:
- Not applicable.
- Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance and the preparation. Check with glove manufacturer for data regarding chemical resistance.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and therefore has to be checked prior to the application.

• Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

(Contd. on page 5)

Ariticle Number 402

Revision Number 3

Fuge 5/8 Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

(Contd. of page 4)

Sa	ıfety glasses
----	---------------

Safety glasses with side shields should be worn. If splashes are likely to occur, wear goggles or a full face mask. Do not wear contace lenses. Eye wash stations and safety showers should be close to workstation.

• Skin and body protection:

Wear protective apron and boots.

Note: All pigments, fillers, fibers and extenders in this product are totally encapsulated and do not pose a respirable dust hazard during installation and use of this products.

Information on basic physical a	ina cnemical properties	
General Information		
Appearance	Fabric	
Form:Color:		
• Color: • Odor:	White or grey No apparent odor.	
 Odor: Odor Threshold: 	No applicable.	
• pH-value:	Not applicable.	
*	Tor approacte.	
Change in condition		
 Melting point/Melting Range 	Not applicable	
Boiling point/Boiling Range	Not applicable.	
• Auto igniting:	Not applicable	
• Danger of explosion:	Product is not explosive.	
Information on basic physical a	and chemical properties	
Explosion limits		
Lower:	Not applicable	
Upper:	Not applicable	
• Density (lb./gal):	Not applicable	
• Evaporation rate:	Not deterimined	
• Partition coefficient		
(n-octanol/water: gravity:	Not determined	
• VOC (EPA Method 24A):	Not applicable	
• Solubility in / Miscibility with		
Water:	Insoluble	
Otherinformation	No further relevent information	

Section 10. Stability and reactivity

Reactivity

Chemical stability

- *Thermal decomposition/conditions to be avoided:* No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- Conditions to avoid:

acc. to OSHA HCS

Ariticle Number 402

Revision Number 3

Page 6/8 Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

Heat, open flames, and sparks. Keep away from direct sunlight. Do not allow vapor to accumulate in low or confined areas Do not pressurize, cut, weld, braze, drill, or grind on containers. Situations conducive to the build up of static electricity.

• Incompatible materials: Acids, alkalis, and oxidizing agents.

- *Hazardous decomposition products: CO*, *H*₂*S*, *CO*₂ *and SOX*
- Hazardous polymerization: None

Section 11. Toxicological information

Information on toxicological effects

- ORAL rat LD50 (mg/kg):
- Dermal rabbit LD50 (mg/kg):
- Eye irritation rabbit:
- Skin irritation rabbit (24-hr exposure):

Information on acute toxicity

- Acute toxicity
- Primary irritant effect
- on the skin:
- May irritate the eye.

 on the eye:
- May irritate the eye. • Sensitization: No sensitizing effects known.

Additional toxicological information:

Carcinogenic catagories

IARC (International Agency for Reserarch on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Section 12. Ecological information

Toxicity

- Aquatic toxicity:
- No further relevent information available.
- *Persistance and degradability:* No further relevent information available.
- Bioaccumulative potential: No further relevent information available.
 Mobility in poil.
- *Mobility in soil:* No further relevent information available.

No data availble No data availble No data available No data available (Contd. of page 5)

(Contd. on page 7)

acc. to OSHA HCS

Ariticle Number 402

Revision Number 3

Revision Date 01/05/2016

Tradename: Re-Flex Flashing Fabric

- Additional ecological information:
- General notes: At present there are no ecotoxicological assessments.

Results of PBT and vPvB assessment

- **PBT**:
 - Not applicable.
- vPvB:

Not applicable.

Other adverse effects

No further relevant informatio available.

Section 13. Disposal considerations

Waste treatment methods

• Recommendation:

The generation of waste should be avoided or minimized whenever and wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental and waste disposal legislation and all local, regional, and federal authority requirements. Dispose of surplus and non-recyclable products thru a licensed waste disposal contractor. Waste should not be allowed to enter streams, lakes, sewer systems, or other open waterways. Waste packaging should be recycled. This material and its containers that have not been cleaned or rinsed out may contain product residues or vapors that are highly flammable and may explode. Do not cut, weld, or grind used containers. Do not dispose with household garbage. Any contaminated cleaning materials used with this product must be properly disposed and treated as flammable materials unless they have been thoroughly washed and clean of any product or residue. Do not allow product to reach sewage system.

Uncleaned packagings

• **Recommendation**: Disposal must be made in compliance with local, state, regional, and federal regulations.

Section 14. Transportion information UN proper shipping name • *DOT* Not Regulated ADR Not Regulated Not Regulated • IMDG, IATA Transport hazard class(es) • *DOT* Not classified as a hazardous material under HM-181 • Canadian TDG: Not determined

Safety, health and environmental regulations/legislation specific for the substance or mixture • Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

(Contd. on page 8)

Page 7/8



acc. to OSHA HCS Revision Number 3

Revision Date 01/05/2016

Ariticle Number 402

(Contd. of page 7)

Page 8/8

Tradename: Re-Flex Flashing Fabric

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

Proposition 65

- Chemicals known to cause cancer: Warning: This product may contain chemical(s) known to the state of California to cause cancer, birth defects, and/or other reproductive harm.
- Chemicals known to cause reproductive toxicity: Warning: This product contains a chemical(s) known to the state of California to cause birth defects or other reproductive harm.

(DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

Cancerogenity categories

• EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

• MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

National regulations:

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Section 16. Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Roofing Products International, Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Roofing Products International, Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- Department issuing SDS: Technical Services Department
- Creation Date: 03/21/2007
- Date of preparation: 01/05/2016
- Last revision: 01/05/2016
- Reason for revision: Format Update Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) DOT: US Department of Transportation ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) IMDG: International Maritime Code for Dangerous Drugs Flam. Liq. 0: Flammable liquids, Hazard Catagory 0 Asp. Tox. 1: Aspiration hazard, Hazard Catagory 1

End of SDS